


Installation Manual

8XAES-PCC-DMA

Pin converter board for DB25 AES connections

Warranty information can be found at www.odyssey-products.com



The Model 8XAES-PCC-DM pin-configuration changer, with DMA8/Dolby pinned input to Doremi/DCI pinned output.

Input connector: DB25 female with jackscrews, pin-configured to accept “DMA8”, “Dolby”, “JSD-80”, and “Sony” cables.

Output connector: DB25 male with lockdown screw, secures to devices “Doremi” or “DCI” input connectors. Also known as the “TASCAM” pinout.

	(Input)		(Output)	
	Channel	DB25F “DMA/Dolby”	DB25M “DOREMI/DCI”	
(Output) DB25 Male “DOREMI/DCI” Pin-configuration	1/2 plus	14	24	(Left / Right)
	1/2 minus	2	12	
	1/2 ground	1	25	
	3/4 plus	3	10	(Center / Subwoofer)
	3/4 minus	16	23	
	3/4 ground	4	11	
	5/6 plus	17	21	(LS / RS)
	5/6 minus	5	9	
	5/6 ground	18	22	
	7/8 plus	6	7	(LEX / REX) / (Europe: HI / VI)
	7/8 minus	19	20	
	7/8 ground	7	8	
	9/10 plus	8	18	(TBD)
	9/10 minus	21	6	
	9/10 ground	20	19	
	11/12 plus	22	4	(BSL / BSR)
	11/12 minus	10	17	
	11/12 ground	9	5	
	13/14 plus	11	15	(TBD)
	13/14 minus	24	3	
	13/14 ground	23	16	
	15/16 plus	25	1	(HI / VI)
	15/16 minus	13	14	
	15/16 ground	12	2	